



2002 DYNA GLIDE SPECIFICATIONS¹: FXDWG WIDE GLIDE

DIMENSIONS

Length	2381 mm
Seat Height (measure laden w/ 82 kg rider)	680 mm
Ground Clearance	136.5 mm
Rake	32 degrees
Trail	129.5 mm
Wheelbase	1665 mm
Tyres: Dunlop Harley-Davidson Series D401/ D402	
Front Size	MH90-21 54H
Rear Size	150/80B16 71H
Fuel Capacity (includes 1.1 gal. reserve tank)	19.7 L
Reserve Fuel Capacity	4.2 L
Oil Capacity	2.8 L
Empty Weight	300 kg

ENGINE²

Engine	Twin Cam 88 (vibration isolation-mounted)
Valves	Pushrod-operated overhead valves; with hydraulic self-adjusting lifters; two valves per cylinder
Bore and Stroke	95.3 x 101.6 mm
Displacement	1449 cc
Compression Ratio	8.8:1
Fuel System	Carburation (40 mm constant velocity with enricher and accelerator pump)
Air Cleaner/Filter	Oval with spun aluminium insert; high-efficiency, pleated paper filtration
Ignition	Single-fire, non-wasted, map-controlled spark ignition system; electronic breakerless with multiple advance curve matrix
Lubrication System	Dry sump, internally mounted, crank driven gerotor pressure and dual scavenge pump with spin on 10µ pressurised oil filter

DRIVETRAIN

Primary Drive	Double-row chain; oil bath; mechanical tensioner; 25/36-tooth sprockets (1.44:1)
Final Drive	Gates aramid fibre reinforced Poly Chain belt; 32/70-tooth sprockets; 2.188:1
Clutch	Multi-plate with diaphragm spring in oil bath
Transmission	Five-speed, constant mesh
Gear Ratio:	
1st	3.21
2nd	2.21
3rd	1.57
4th	1.23
5th	1.00

CHASSIS

Frame	Mild steel, rectangular section backbone with twin down-tubes
Swing Arm	Mild steel, rectangular section
Front Fork	Wide, 41.3 mm dia. forks with chrome fork triple clamp
Rear Shocks	Chrome coil-over with adjustable spring preload
Wheels	19 in. front; 16 in. rear disc, laced
Brakes:	
Calliper type	Four-piston front and rear
Rotor type (diameter x width):	Patented, Uniform Expansion Rotors
Front	292 mm
Rear	292 mm
Suspension travel:	
Front wheel	142.5 mm
Rear wheel	109 mm

PERFORMANCE

Engine Torque	106 NM @ 2900 rpm
Braking at 96.6 kph:	
Maximum load	49.5 m
Lean Angle (per SAEJ1168):	
Right	31 degrees
Left	32 degrees

ELECTRIC

Battery	Sealed 12-volt, 19 amp-hour, 270cca (per Battery Council International rating)
Charging	364 watts @ 3,000 rpm, 416 watts peak
Starting	1.2 kw electric with Bendix-type engagement
Lights:	(As per country regulation)
Headlamp	Quartz halogen 55-watt low beam, 60-watt high beam
Tail/stop lights	5w/21w
Turn signal lights	21w self-cancelling
Running lights	Integrated in front turn signals (except where prohibited by law)
Indicator lamps	High beam, neutral, oil pressure, engine diagnostic light, turn signals and security system (optional)

STYLING/CONVENIENCE

Engine Trim	Black powdercoat with chrome covers
Exhaust System	Staggered chrome shorty duals with low interconnect
Oil Tank	Under-transmission
Front Fender	Custom with painted brace
Rear Fender	Custom sculpted Bobtail with chrome supports
Handlebars	Mini Ape-hanger with chrome riser
Windshield	none
Footpegs	Rubber-isolated operator and rubber-covered passenger
Forward foot position	Redesigned forward brake and shift lever controls
Seat	Custom, stepped chopper seat with tucked pillow-look
Passenger Backrest	Chrome sideplates and sissy bar with H-D Eagle emblem and padded backrest
Saddlebags	none
Instruments	Large, tank-mounted electronic speedometer with odometer and resettable tripmeter in chrome tank console; fuel gauge
Fork Lock	Barrel-key on steering head, key common with ignition

COLOURS³

Vivid Black, Diamond Ice Pearl, Luxury Rich Red Pearl, Concord Purple Pearl, Two-Tone Luxury Rich Red/Black, Two-Tone Luxury Blue/Diamond Ice Real Red Pearl, Impact Blue Pearl

SERVICING

Service Interval	First 1,600 Km; every 8,000 Km thereafter. – Inspections of certain systems and components are required at 4,000 Km intervals
------------------	--

¹ Harley-Davidson reserves the right to discontinue models or change specifications at any time without incurring any obligations. Vehicle specifications may vary from country to country depending on local laws, and some models are not available in certain countries.

² Additional Twin Cam 88 specs available.

³ Availability may vary from dealer to dealer, and is subject to change without notice.