



2002 DYNA GLIDE SPECIFICATIONS¹: FXDXT SUPER GLIDE T-SPORT

DIMENSIONS

Length	2310 mm
Seat Height (measure laden w/ 82 kg. rider)	708 mm
Ground Clearance	149.2 mm
Rake	28 degrees
Trail	104.1 mm
Wheelbase	1580 mm
Tyres: Dunlop Harley-Davidson Series D401	
Front	100/90-19 57H
Rear	150/80B16 71H
Fuel Capacity (includes 0.9 gal. reserve)	18.5 L
Reserve Fuel Capacity	3.4 L
Oil Capacity	2.8 L
Empty Weight	315 kg

ENGINE²

Engine	Twin Cam 88 (vibration isolation-mounted)
Valves	Pushrod-operated overhead valves; with hydraulic self-adjusting lifters; two valves per cylinder
Bore and Stroke	95.3 x 101.6 mm
Displacement	1449 cc
Compression Ratio	8.8:1
Fuel System	Carburation (40 mm constant velocity with enricher and accelerator pump)
Air Cleaner/Filter	Oval with spun aluminium insert; high-efficiency, pleated paper filtration
Ignition	Single-fire, non-wasted, map-controlled spark ignition system; electronic breakerless with multiple advance curve matrix
Lubrication System	Dry sump, internally mounted, crank driven gerotor pressure and dual scavenge pump with spin on 10µ pressurised oil filter

DRIVETRAIN

Primary Drive	Double-row chain; oil bath; mechanical tensioner;
	25/36-tooth sprockets (1.44:1)
Final Drive	Gates aramid fibre reinforced Poly Chain belt; 32/70-tooth sprockets; 2.188:1
Clutch	Multi-plate with diaphragm spring in oil bath
Transmission	Five-speed, constant mesh
Gear Ratio:	
1st	3.21
2nd	2.21
3rd	1.57
4th	1.23
5th	1.00

CHASSIS

Frame	Mild steel, rectangular section backbone with twin down-tubes
Swing Arm	Mild steel, rectangular section
Front Fork	Premium, 39 mm with polished aluminium fork triple clamp, adjustable compression and rebound damping and dual-rate springs with externally adjustable preload
Rear Shocks	Premium sport shocks with adjustable rebound damping and blacked-out, dual-rate springs with externally adjustable preload
Wheels	19 in. front, 16 in. rear, 13-spoke black/silver cast aluminium alloy
Brakes:	
Calliper type	Four-piston front and rear
Rotor type (diameter):	Patented, Uniform Expansion Rotors
Front (DUAL)	292 mm
Rear	292 mm
	Suspension travel:
Front wheel	155 mm
Rear wheel	124.5 mm

PERFORMANCE

Engine Torque	106 NM @ 2900 rpm
Braking at 96.6 kph:	
Maximum load	46.5 m
Lean Angle (per SAEJ1168):	
Right	32.4 degrees
Left	34.4 degrees

ELECTRIC

Battery	Sealed 12-volt, 19 amp-hour, 270cca (per Battery Council International rating)
Charging	364 watts @ 3,000 rpm, 416 watts peak
Starting	1.2 kw electric with Bendix-type engagement
Lights:	(As per country regulation)
Headlamp	Quartz halogen 55-watt low beam, 60-watt high beam
Tail/stop lights	5w/21w
Turn signal lights	21w self-cancelling
Running lights	Integrated in front turn signals (except where prohibited by law)
Indicator lamps	High beam, neutral, oil pressure, engine diagnostic light, turn signals and security system (optional)

STYLING/CONVENIENCE

Engine Trim	Black powdercoat with wrinkle black and texture black covers
Exhaust System	Staggered chrome shorty duals with low interconnect
Oil Tank	Under-transmission
Front Fender	Sport-style with painted brace
Rear Fender	Sport wrap-around with wrinkle black supports
Handlebars	Flat "XR" style, 31.5 in. wide, black
Fairing	Sport half-fairing with tinted adjustable windshield
Footpegs	Rubber-isolated operator and rubber covered passenger
Forward Foot Position	Frame-mounted highway pegs (not all destinations)
Seat	Custom touring saddle with generous passenger pillion
Passenger Backrest	none
Saddlebags	Quick-detach, ballistic nylon saddlebags with zipper-cinch expandability, dual compartments, water-resistant nylon inner bag, rain-cover, and premium leather tops, expanded 22 Litres, unexpanded 12 Litres
Instruments	Electronic speedometer with odometer and resettable tripmeter; tachometer, fuel gauge
Fork Lock	Barrel-key on steering head, key common with ignition

COLOURS³

Vivid Black, Luxury Rich Red Pearl, Diamond Ice Pearl, Suede Green Pearl, Luxury Blue Pearl, Jade Sunglo Pearl

SERVICING

Service Interval	First 1,600 Km; every 8,000 Km thereafter. – Inspections of certain systems and components are required at 4,000 Km intervals
------------------	--

¹ Harley-Davidson reserves the right to discontinue models or change specifications at any time without incurring any obligations. Vehicle specifications may vary from country to country depending on local laws, and some models are not available in certain countries.

² Additional Twin Cam 88 specs available.

³ Availability may vary from dealer to dealer, and is subject to change without notice.